SAFETY DATA SHEET

n-Butylamine
10440

Version / Revision	4	**Revision Date**	11-Apr-2025
Supersedes Version	3.01***	**Issuing date**	11-Apr-2025

SECTION 1: Identification of the substance / mixture and of the company / undertaking

1.1. Product identifier

Identification of the substance/preparation **n-Butylamine**

CAS-No 109-73-9
EC No. 203-699-2

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the Substance / Preparation Intermediate.
Uses advised against None

1.3. Details of the supplier of the safety data sheet

Company/Undertaking Identification
OXEA GmbH
Rheinpromenade 4A
D-40789 Monheim
Germany***

Product Information
Product Stewardship
FAX: +49 (0)208 693 2053
email: sc.psq@oxea.com

1.4. Emergency telephone number

Emergency telephone number +44 (0) 1235 239 670 (UK) available 24/7
NCEC +1 202 464 2554

Local emergency telephone number
+61 2 8014 4558 (Australia)
18000 74234 (Australia toll-free number)
+64 9 929 1483 (New Zealand)
0800 446 881 (New Zealand toll-free number)
+65 3158 1195 (Sri Lanka)
007 803 011 0293 (Indonesia toll-free number)
+60 3 6207 4347 (Malaysia)
001 800 120 666 751 (Thailand toll-free number)
+65 3158 1200 (Bangladesh)
+63 2 8231 2149 (Philippines)
+84 28 4458 2388 (Vietnam)
+65 3165 2217 (Singapore)
available 24/7

SECTION 2: Hazards identification

Europe

2.1. Classification of the substance or mixture

This substance is classified based on Directive 1272/2008/EC and its amendments (CLP Regulation)

Flammable liquid Category 2, H225
Acute oral toxicity Category 4, H302
Acute dermal toxicity Category 3, H311
Acute inhalation toxicity Category 3, H331
Skin corrosion/irritation Category 1A, H314
Serious eye damage/eye irritation Category 1, H318
Target Organ Systemic Toxicant - Single exposure Category 3, H335

Additional information
For full text of Hazard- and EU Hazard-statements see SECTION 16.

2.2. Label elements

Labelling according to Regulation 1272/2008/EC and its amendments (CLP Regulation).

Hazard pictograms



Signal word **Danger**

Hazard statements
H225: Highly flammable liquid and vapour.
H302: Harmful if swallowed.
H311: Toxic in contact with skin.
H331: Toxic if inhaled.
H314: Causes severe skin burns and eye damage.
H335: May cause respiratory irritation.

Precautionary statements
P210: Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P233: Keep container tightly closed.
P260: Do not breathe gas/mist/vapours.
P280: Wear protective gloves/protective clothing/eye protection/face protection.
P301 + P330 + P331: IF SWALLOWED: Rinse mouth. Do NOT induce vomiting.
P321: Specific treatment: IF ON SKIN: Wash off with 3% acetic acid followed by large amounts of plain water for at least 5 min as a final step.
P304 + P340: IF INHALED: Remove person to fresh air and keep comfortable for breathing.
P305 + P351 + P338: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P310: Immediately call a POISON CENTER/doctor.
P403 + P235: Store in a well ventilated place. Keep cool.

2.3. Other hazards

Vapour is heavier than air and can travel considerable distance to a source of ignition and flashback
Components of the product may be absorbed into the body by inhalation and through the skin

PBT and vPvB assessment This substance is not considered to be persistent, bioaccumulating nor toxic (PBT), nor very persistent nor very bioaccumulating (vPvB)

USA

2.1. Classification of the substance or mixture

This substance is classified in accordance with paragraph (d) of §1910.1200 (GHS-US classification).

Acute oral toxicity Category 4, H302
Acute dermal toxicity Category 3, H311
Acute inhalation toxicity Category 3, H331
Skin corrosion/irritation Category 1A, H314
Serious eye damage/eye irritation Category 1, H318
Target Organ Systemic Toxicant - Single exposure Category 3, H335
Flammable liquid Category 2, H225
Environmental hazard Aquatic Acute 2; H401

OSHA Specified Hazards Not applicable.

2.2. Label elements

Labeling according to §1910.1200 (GHS-US labeling).

Hazard symbol(s)



Signal word **Danger**

Hazard statements

H225: Highly flammable liquid and vapor.
H302: Harmful if swallowed.
H311 + H331: Toxic in contact with skin or if inhaled.
H314: Causes severe skin burns and eye damage.
H335: May cause respiratory irritation.
H401: Toxic to aquatic life

Precautionary statements

Prevention

P210: Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P233: Keep container tightly closed.
P240: Ground and bond container and receiving equipment.
P241: Use explosion-proof electrical/ ventilating/ lighting equipment.
P242: Use non-sparking tools.
P243: Take precautionary measures against static discharge.
P260: Do not breathe gas/mist/vapours.

	P264: Wash hands thoroughly after handling. P270: Do not eat, drink or smoke when using this product. P271: Use only outdoors or in a well ventilated area. P273: Avoid release to the environment. P280: Wear protective gloves/protective clothing/eye protection/face protection.
Response	P301 + P330 + P331: IF SWALLOWED: Rinse mouth. Do NOT induce vomiting. P321: Specific treatment: IF ON SKIN: Wash off with 3% acetic acid followed by large amounts of plain water for at least 5 min as a final step. P361: Take off immediately all contaminated clothing and wash it before reuse. P304 + P340: IF INHALED: Remove person to fresh air and keep comfortable for breathing. P305 + P351 + P338: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. P310: Immediately call a POISON CENTER/doctor.
Storage	P403 + P235: Store in a well ventilated place. Keep cool. P405: Store locked up.
Disposal	P501: Dispose of contents/container in accordance with local regulation.

2.3. Other hazards

Vapour is heavier than air and can travel considerable distance to a source of ignition and flashback
Components of the product may be absorbed into the body by inhalation and through the skin

SECTION 3: Composition / information on ingredients

3.1. Substances

Component	CAS-No	REACh-No	1272/2008/EC	Concentration (%)
Butylamine	109-73-9	01-2119470233-46	Flam. Liq. 2; H225 Acute Tox. 4; H302 Acute Tox. 3; H311 Acute Tox. 3, H331 Skin Corr. 1A; H314 Eye Dam. 1; H318 STOT SE 3; H335 (>=1%) ATE = 372 mg/kg (oral) ATE = 429 mg/kg (dermal) ATE = 4,3 mg/L*** (inhalation) (vapours)***	> 99,5

SECTION 4: First aid measures

4.1. Description of first aid measures

Inhalation
Keep at rest. Aerate with fresh air. Call a physician immediately. Symptoms of poisoning may develop many hours

after exposure.

Eyes
Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Remove contact lenses. Immediate medical attention is required.

Skin
Wash off with 3% acetic acid followed by large amounts of plain water for at least 5 min as a final step. Immediate medical treatment is necessary as untreated wounds from corrosion of the skin heal slowly and with difficulty.

Ingestion
Call a physician immediately. Do not induce vomiting without medical advice.

4.2. Most important symptoms and effects, both acute and delayed

Main symptoms
shortness of breath, convulsions, cough, hypertensive effect, headache, vomiting, allergic reactions, nausea, unconsciousness.

Special hazard
Stomach perforation, Lung oedema.

4.3. Indication of any immediate medical attention and special treatment needed

General advice
Remove contaminated, soaked clothing immediately and dispose of safely. First aider needs to protect himself.

Treat as an alkaline substance (similar to ammonia). If ingested, irrigate the stomach. Treat skin and mucous membranes with antihistamine and corticoids. In case of lung irritation, first treatment with cortisone spray. Symptoms may be delayed. Later control for pneumonia and lung oedema.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media
alcohol-resistant foam, dry chemical, carbon dioxide (CO2), water spray

Unsuitable Extinguishing Media
Do not use a solid water stream as it may scatter and spread fire.

5.2. Special hazards arising from the substance or mixture

Under conditions giving incomplete combustion, hazardous gases produced may consist of:
carbon monoxide (CO)
carbon dioxide (CO2)
nitrogen oxides (NOx)
Combustion gases of organic materials must in principle be graded as inhalation poisons
Vapour is heavier than air and can travel considerable distance to a source of ignition and flashback

5.3. Advice for firefighters

Special protective equipment for firefighters
Fire fighter protection should include a self-contained breathing apparatus (NIOSH-approved or EN 133) and full fire-fighting turn out gear.

Precautions for firefighting
Cool containers / tanks with water spray. Dike and collect water used to fight fire. Water run-off and vapor cloud may be corrosive. Keep people away from and upwind of fire.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

For non-emergency personnel: For personal protective equipment see section 8. Avoid contact with skin and eyes. Avoid breathing vapors or mists. Keep people away from and upwind of spill/leak. Ensure adequate ventilation, especially in confined areas. Keep away from heat and sources of ignition.
For emergency responders: Personal protection see section 8.

6.2. Environmental precautions

Prevent further leakage or spillage. Do not discharge product into the aquatic environment without pretreatment (biological treatment plant).

6.3. Methods and material for containment and cleaning up

Methods for containment
Stop the flow of material, if possible without risk. Dike spilled material, where this is possible.

Methods for cleaning up
Soak up with inert absorbent material. DO NOT use combustible materials such as sawdust. Keep in suitable, closed containers for disposal. If liquid has been spilt in large quantities clean up promptly by scoop or vacuum. Dispose of in accordance with local regulations. Take necessary action to avoid static electricity discharge (which might cause ignition of organic vapours).

6.4. Reference to other sections

For personal protective equipment see section 8.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Advice on safe handling
Avoid contact with skin, eyes and clothing. Do not use compressed air for filling, discharging or handling. Wash hands before breaks and immediately after handling the product. Provide sufficient air exchange and/or exhaust in work rooms. Refill and handle product only in closed system.

Hygiene measures
When using, do not eat, drink or smoke. Take off all contaminated clothing immediately. Wash hands before breaks and immediately after handling the product.

Advice on the protection of the environment
See Section 8: Environmental exposure controls.

Incompatible products
strong acids
oxidizing agents

7.2. Conditions for safe storage, including any incompatibilities

Advice on protection against fire and explosion
Keep away from sources of ignition - No smoking. Take necessary action to avoid static electricity discharge (which might cause ignition of organic vapours). In case of fire, emergency cooling with water spray should be available. Ground and bond containers when transferring material. Vapour is heavier than air and can travel considerable distance to a source of ignition and flashback.

Technical measures/Storage conditions
Keep containers tightly closed in a cool, well-ventilated place. Handle and open container with care. Handle under nitrogen, protect from moisture. Keep at temperatures between -18 and 38 °C (0 and 100 °F).

Temperature class
T2

7.3. Specific end use(s)

Intermediate
Formulation
Distribution of substance
laboratory chemicals

SECTION 8: Exposure controls / personal protection

8.1. Control parameters

Exposure limits European Union

No exposure limits established

Exposure limits Germany

TRGS 900

Component	AGW (mg/m³)	AGW (ppm)	STEL factor Peak factor	Peak-limit category
Butylamine CAS: 109-73-9	6.1	2	2 2.5	I

Component	Skin resorptive	Reproductive hazard	Note
Butylamine CAS: 109-73-9		Y	

MAK-values from the DFG

Component	MAK (ppm)	MAK (mg/m³)	listed w/o limits	Ceiling limit value
Butylamine CAS: 109-73-9	2	6.1		(2) I

Component	H;S	carcinogenic category	pregnancy group	mutagenicity category
Butylamine CAS: 109-73-9			C	

Note
For details and further information please refer to the original regulation.

Exposure limits United States of America

US ACGIH

Component	Ceiling (mg/m³)	Ceiling (ppm)	Skin Absorption	Sensitization
Butylamine CAS: 109-73-9		5	Yes	

US OSHA Z-1

Component	Ceiling (mg/m³)	Ceiling (ppm)	PEL (mg/m³)	PEL (ppm)	Skin Designation
Butylamine CAS: 109-73-9	15	5			Yes

Note
For details and further information please refer to the original regulation.

8.2. Exposure controls

Appropriate Engineering controls
General or dilution ventilation is frequently insufficient as the sole means of controlling employee exposure. Local ventilation is usually preferred. Explosion-proof equipment (for example fans, switches, and grounded ducts) should be used in mechanical ventilation systems.

Personal protective equipment

General industrial hygiene practice
Avoid contact with skin, eyes and clothing. Do not breathe vapours or spray mist. Ensure that eyewash stations and safety showers are close to the workstation location.

Hygiene measures
When using, do not eat, drink or smoke. Take off all contaminated clothing immediately. Wash hands before breaks and immediately after handling the product.

Eye protection
Tightly fitting safety goggles. In addition to goggles, wear a face shield if there is a reasonable chance for splash to the face.

Hand protection
Wear protective gloves. Recommendations are listed below. Other protective material may be used, depending on the situation, if adequate degradation and permeation data is available. If other chemicals are used in conjunction with this chemical, material selection should be based on protection for all chemicals present.

Suitable material	Viton
Evaluation	according to EN 374: level 3
Glove thickness	approx 0,5 mm
Break through time	approx 40 min

Suitable material	polyvinylchloride
Evaluation	Information derived from practical experience
Glove thickness	approx 0,8 mm

Skin and body protection
Impervious clothing. Wear face-shield and protective suit for abnormal processing problems.

Respiratory protection
Respirator with filter for ammonia vapour and ammonia derivatives (K Filter). Use the indicated respiratory protection if the occupational exposure limit is exceeded and/or in case of product release (dust). Equipment should conform to NIOSH, EN or other applicable national standards.

Environmental exposure controls
Use product only in closed system. If leakage can not be prevented, the substance needs to be suck off at the emersion point, if possible without danger. Observe the exposure limits, clean exhaust air if needed. If recycling is not practicable, dispose of in compliance with local regulations. Inform the responsible authorities in case of leakage into the atmosphere, or of entry into waterways, soil or drains.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Appearance	liquid @ 20 °C (68 °F)
Colour	colourless
Odour	ammonia-like
Odour threshold	1,8 µl/l
pH	13 (50 % in water @ 25 °C (77 °F)) DIN 19268
Melting point/freezing point	-47 °C (Pour point) @ 1013 hPa
Boiling point or initial boiling point and boiling range	77 °C @ 1013 hPa
Flash point	-7,5 °C
Method	ISO 13736
Evaporation rate	No data available
Flammability (solid, gas)	Does not apply, the substance is a liquid
Lower explosion limit	1,7 Vol %
Upper explosion limit	10 Vol %

Vapour pressure

Values [hPa]	Values [kPa]	Values [atm]	@ °C	@ °F	Method
102	10,2	0,101	20	68	DIN EN 13016-2
369	36,9	0,364	50	122	DIN EN 13016-2

Relative vapour density 2,5 (Air = 1) @ 20 °C (68 °F)

Density and/or relative density

Values	@ °C	@ °F	Method
0,736	20	68	DIN 51757

Solubility	> 424 g/l @ 20 °C, miscible, in water, OECD 105
Partition coefficient n-octanol/water (log value)	0 @ 25 °C (77 °F) OECD 117
Autoignition temperature	320 °C
Method	DIN 51794
Decomposition temperature	No data available
Viscosity	0,51 mPa*s @ 20 °C
Method	ASTM D445, dynamic
Oxidizing properties	Does not apply, substance is not oxidising. There are no chemical groups associated with oxidizing properties
Explosive properties	Does not apply, substance is not explosive. There are no chemical groups associated with explosive properties

9.2. Other information

Molecular weight	73,14
Molecular formula	C4 H11 N
log Koc	1,64 @ 22,5°C (72,5 °F) OECD 106

Dissociation constant	pKa 10,8 @ 23,5 °C (74,3 °F) OECD 112
Refractive index	1,401 @ 20 °C
Surface tension	69,5 mN/m (1 g/l @ 20°C (68°F)), OECD 115

SECTION 10: Stability and Reactivity

10.1. Reactivity

The reactivity of the product corresponds to the typical reactivity shown by the substance group as described in any text book on organic chemistry.

10.2. Chemical stability

Stable under recommended storage conditions.

10.3. Possibility of hazardous reactions

Hazardous polymerisation does not occur.

10.4. Conditions to avoid

Avoid contact with heat, sparks, open flame and static discharge. Avoid any source of ignition.

10.5. Incompatible materials

strong acids, oxidizing agents.

10.6. Hazardous decomposition products

No decomposition if stored and applied as directed. If heated to thermal decomposition the following decomposition products may occur depending on the conditions. carbon monoxide (CO). nitrogen oxides (NOx). cyanides. nitric acid. nitriles.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Likely routes of exposure Inhalation, Eye contact, Skin contact, Ingestion

Acute toxicity				
Butylamine (109-73-9)				
Routes of Exposure	Endpoint	Values	Species	Method
Oral	LD50	372 mg/kg	rat, male/female	OECD 401
Dermal	LD50	1100 mg/kg	guinea pig male	21 CFR 191.10
Dermal	LD50	429 mg/kg	guinea pig male	21 CFR 191.10
Inhalative	LC50	> 4,2 mg/l (4h)	rat, male/female	OECD 403

Butylamine, CAS: 109-73-9
Assessment
The available data lead to the classification given in section 2

Irritation and corrosion				
Butylamine (109-73-9)				
Target Organ Effects	Species	Result	Method	

Skin	rabbit	corrosive	OECD 404	1 min
Eyes	rabbit	corrosive		
Respiratory tract	mouse	RD50: 84 - 112 ppm		15 - 60 min

Butylamine, CAS: 109-73-9
Assessment
The available data lead to the classification given in section 2

Sensitization				
Butylamine (109-73-9)				
Target Organ Effects	Species	Evaluation	Method	
Skin	guinea pig	not sensitizing	OECD 406	2 %, aqueous solution

Butylamine, CAS: 109-73-9
Assessment
Based on available data, the classification criteria are not met for:
Skin sensitization
For respiratory sensitization, no data are available

Subacute, subchronic and prolonged toxicity				
Butylamine (109-73-9)				
Type	Dose	Species	Method	
Subacute toxicity	NOAEL: < 17 ppm/d (14 d)	rat, female	OECD 412	Inhalation

Butylamine, CAS: 109-73-9
Assessment
Based on available data, the classification criteria are not met for:
STOT RE

Carcinogenicity, Mutagenicity, Reproductive toxicity					
Butylamine (109-73-9)					
Type	Dose	Species	Evaluation	Method	
Mutagenicity		Salmonella typhimurium	negative	OECD 471 (Ames)	In vitro study
Mutagenicity		mouse	negative	OECD 474	in vivo
Mutagenicity		mouse lymphoma cells	negative	OECD 476 (Mammalian Gene Mutation)	In vitro study
Reproductive toxicity	NOAEC: 500 mg/m³	rat, parental		OECD 415	read across
Reproductive toxicity	NOAEC: 500 mg/m³	Rat, prenatal		OECD 415	read across
Developmental Toxicity	LOAEC: 51 mg/m³	rat		OECD 412 Inhalation	Maternal toxicity
Developmental Toxicity	NOAEC: 460 mg/m³	rat		OECD 412 Inhalation	Developmental toxicity
Developmental Toxicity	NOAEL 100 mg/kg/d	rat		OECD 414, Oral	Teratogenicity read across
Developmental Toxicity	NOAEL 400 mg/kg/d	rat		OECD 414, Oral	Maternal toxicity read across
Developmental Toxicity	LOAEL 400 mg/kg/d	rat		OECD 414, Oral	Teratogenicity read across

Butylamine, CAS: 109-73-9
CMR Classification
The available data on CMR properties are summarized in the table above. They do not indicate a classification into categories 1A or 1B
Evaluation
In vitro tests did not show mutagenic effects
No reprotoxic effects in the absence of maternal toxicity
In the absence of specific alerts no cancer testing is required

Butylamine, CAS: 109-73-9
Main symptoms
shortness of breath, convulsions, cough, hypertensive effect, headache, vomiting, allergic reactions, nausea, unconsciousness.
Target Organ Systemic Toxicant - Single exposure
The available data lead to the classification given in section 2
Target Organ Systemic Toxicant - Repeated exposure
Based on available data, the classification criteria are not met for:
STOT RE
Aspiration toxicity
Due to the viscosity, this product does not present an aspiration hazard
Other adverse effects
Components of the product may be absorbed into the body by inhalation and through the skin.
Note
Handle in accordance with good industrial hygiene and safety practice. Further details on substance data can be found in the registration dossier under the following link:
http://echa.europa.eu/information-on-chemicals/registered-substances.

SECTION 12: Ecological information

12.1. Toxicity

Acute aquatic toxicity			
Butylamine (109-73-9)			
Species	Exposure time	Dose	Method
Pimephales promelas (fathead minnow)	96h	LC50: 268 mg/l	OECD 203
Lepomis macrochirus (Bluegill sunfish)	96h	LC50: 32 mg/l	OECD 203
Pseudomonas putida	16 h	NOEC: 65 mg/l	DIN 38412, part 8
Pseudomonas putida	16 h	EC0: > 800 mg/l (neutralized)	DIN 38412, part 8
Daphnia magna (Water flea)	48h	EC50: 8,3 mg/l	Mobility
Daphnia magna (Water flea)	48h	NOEC: 5,7 mg/l	Mobility
Desmodesmus subspicatus	72h	EC50: 17 mg/l (Growth rate)	OECD 201
Menidia beryllina	72h	LC50: 24 mg/l	OECD 203
Pseudomonas putida	16 h	TTC: 800 mg/l (neutralized)	ISO 10712
Pseudomonas putida	16 h	TTC: 65 mg/l (not neutralized)	ISO 10712
Ceriodaphnia dubia	48h	LC50: 8,2 mg/l	Mortality
Ceriodaphnia dubia	48h	NOEC: 5,7 mg/l	Mortality

Long term toxicity				
Butylamine (109-73-9)				
Type	Species	Dose	Method	
Mortality Reproductive toxicity	Ceriodaphnia dubia	LOEC: 2,22 mg/l/7d	OECD 211	
Mortality Reproductive toxicity	Ceriodaphnia dubia	NOEC: 1,09 mg/l (7d)	OECD 211	
Aquatic toxicity	Desmodesmus subspicatus	NOEC: 2,26 mg/l (3d)	OECD 201 Growth inhibition	

12.2. Persistence and degradability

Butylamine, CAS: 109-73-9
Biodegradation
85 % (14 d), activated sludge, aerobic, OECD 301 C.

Abiotic Degradation		
Butylamine (109-73-9)		
Type	Result	Method
Hydrolysis	not expected	
Photolysis	Half-life (DT50): 11,2 h	SRC AOP v1.92

12.3. Bioaccumulative potential

Butylamine (109-73-9)		
Type	Result	Method
log Pow	0 @ 25 °C (77 °F)	OECD 117
BCF	~ 3,2	calculated

12.4. Mobility in soil

Butylamine (109-73-9)		
Type	Result	Method
Surface tension	69,5 mN/m (1 g/l @ 20°C (68°F))	OECD 115
Adsorption/Desorption	log koc: 1,64 @ 22,5 °C (72,5 °F)	OECD 106
Distribution to environmental compartments	Percent distribution in Media: Air: 20,1% Soil: 0,04% Water: 79,8% Sediment: 0,04% Suspended sediment: 0% Biota: 0%	calculated

12.5. Results of PBT and vPvB assessment

Butylamine, CAS: 109-73-9
PBT and vPvB assessment
This substance is not considered to be persistent, bioaccumulating nor toxic (PBT), nor very persistent nor very bioaccumulating (vPvB)

12.6. Other adverse effects

Butylamine, CAS: 109-73-9
No data available

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Product Information
Disposal required in compliance with all waste management related state and local regulations. The choice of the appropriate method of disposal depends on the product composition by the time of disposal as well as the local statutes and possibilities for disposal.
Hazardous waste according to European Waste Catalogue (EWC)

Uncleaned empty packaging
Contaminated packaging should be emptied as far as possible and after appropriate cleansing may be taken for reuse.

SECTION 14: Transport information

Section 14.1 - 14.6

ICAO-TI / IATA-DGR

14.1. UN number or ID number	UN 1125
14.2. UN proper shipping name	n-Butylamine
14.3. Transport hazard class(es)	3
Subsidiary Risk	8
14.4. Packing group	II
14.5. Environmental hazards	no
14.6. Special precautions for user	no data available

IMDG

14.1. UN number or ID number	UN 1125
14.2. UN proper shipping name	Butylamine
14.3. Transport hazard class(es)	3
Subsidiary Risk	8
14.4. Packing group	II
14.5. Environmental hazards	no
14.6. Special precautions for user	
EmS	F-E, S-C
14.7. Transport in bulk according to Annex II of MARPOL and the IBC Code	
Product name	Butylamine
Ship type	2
Pollution category	Y

ADR/RID

14.1. UN number or ID number	UN 1125

14.2. UN proper shipping name	n-Butylamine
14.3. Transport hazard class(es)	3
Subsidiary Risk	8
14.4. Packing group	II
14.5. Environmental hazards	no
14.6. Special precautions for user	
ADR Tunnel restriction code	(D/E)
Classification Code	FC
Hazard Number	338

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Regulation 1272/2008, Annex VI

Butylamine, CAS: 109-73-9

Classification	Flam. Liq. 2; H225 Acute Tox. 4*; H332 Acute Tox. 4*; H312 Acute Tox. 4*; H302 Skin Corr. 1A; H314 STOT SE 3; H335 (C>=1%)
Hazard pictograms	GHS02 Flame GHS05 Corrosion GHS07 Exclamation mark
Signal word	Danger
Hazard statements	H225, H302, H312, H314, H332, H335

DI 2012/18/EU (Seveso III)

Category	Annex I, part 1: H2 P5a - c; depending on conditions

VOC according to DI 2010/75/EU (Industry Emission Directive)

Component	Status
Butylamine CAS: 109-73-9	regulated

International Inventories

Butylamine, CAS: 109-73-9

AICS (AU)
DSL (CA)
IECSC (CN)
EC-No. 2036992 (EU)
ENCS (2)-132 (JP)
ISHL (2)-132 (JP)
KECI KE-03750 (KR)
INSQ (MX)

PICCS (PH)
TSCA (US)
NZIoC (NZ)***
TCSI (TW)

SECTION 16: Other information

Full text of H-Statements referred to under sections 2 and 3
H225: Highly flammable liquid and vapour.
H302: Harmful if swallowed.
H311: Toxic in contact with skin.
H331: Toxic if inhaled.
H314: Causes severe skin burns and eye damage.
H318: Causes serious eye damage.
H335: May cause respiratory irritation.

Abbreviations
A table of terms and abbreviations can be found under the following link:
http://echa.europa.eu/documents/10162/13632/information_requirements_r20_en.pdf

Training advice
For effective first-aid, special training / education is needed.

Sources of key data used to compile the datasheet
Information contained in this safety data sheet is based on OXEA owned data and public sources deemed valid or acceptable. The absence of data elements required by OSHA, ANSI or Annex II, Regulation 1907/2006/EC indicates, that no data meeting these requirements is available.

Further information for the safety data sheet
Changes against the previous version are marked by ***. Observe national and local legal requirements. For more information, other material safety data sheets or technical data sheets please consult the OXEA homepage (www.oxae.com).

Disclaimer
For industrial use only. The information contained herein is accurate to the best of our knowledge. We do not suggest or guarantee that any hazards listed herein are the only ones which exist. OXEA makes no warranty of any kind, express or implied, concerning the safe use of this material in your process or in combination with other substances. User has the sole responsibility to determine the suitability of the materials for any use and the manner of use contemplated. User must meet all applicable safety and health standards.

End of Safety Data Sheet